

ULTIMA SERIES COVERMATE II™ Cover Handling System

PATENT PENDING



- SIZE** - 34" wide x 13'2" long x 5'6" high (6 and 8 roller models), 10 roller models 6'6" high.
- FRAME*** - 1 1/2" & 2" tubular frame.
- FINISH** - Powder coated, scratch resistant, durable SILVER finish.
- OUTRIGGERS*** - Retractable with adjustable casters to prevent tipping. Safety orange color.
- BRAKES*** - 2 floor locking brakes one at either end of unit.
- CASTERS*** - Six non-marking, 6" Colson casters, three at each end, one of which is offset. Minimum 3/4" tread thickness.
- ROLLER COLLARS*** - Bright yellow collar on each end of every roller to eliminate finger pinching.
- ROLLER BRACKETS*** - Made of polycarbonate with delrin bearings. Mounted with 1/8" shock absorbing rubber pads.
- ROLLER SAFETY*** - Safety bolt on each bracket to prevent roller 'pop-ups'.
- ROLLERS** - Zinc-flo coated for cleaner handling, 2 1/2" diameter.
- FASTENING CLIPS*** - 4 bright yellow, push-on clips for each roller.
- LOADING** - 2 polycarbonate hand cranks or optional power winder.
- CAPACITY*** - Engineered certified load capacity of 5400 lbs.
- PSI POINT LOADING*** - 6 caster design achieves 33% lower point load than 4 caster design.
- WARRANTY** - Ultima Series COVERMATE II™ is warranted for a period of 20 years against defects in materials and workmanship.
- ASSEMBLY** - Required.

* Each Ultima Series Gym Floor Cover and COVERMATE II™ is manufactured to **SAFETY 1ST** engineered standards

POWERMATE™ POWER WINDER




- DIMENSIONS** - 17.3" x 3.3" x 7.7".
- WEIGHT** - 7.7 lbs.
- NOISE RATING*** - Emission at workplace 83 Db.
- MOTOR*** - 110V/1200W/50-60 Hz.
- Forward/reverse switch.
- Thermal overload protection, automatic disconnect includes reset button.
- GEAR HEAD** - Automatic infinitely variable rotation 35-27 rpm.
- GEAR** - Plastic coated aluminum.
- STORAGE** - Includes storage/carrying case.
- WARRANTY** - 10 years against defects in materials and workmanship.
- HOUSING** - Bright yellow glass fibre reinforced.

ULTIMA SERIES COVERCLEAN™ DUAL BRUSH SYSTEM

PATENTED



- MOUNTING** - Quick connect/disconnect, 15/8", 14 gauge drawn channel mounts on both sides of system.
- BRUSH ANGLE** - Brush is mounted at a 35° angle to match path of cover travel at each roller height.
- BRUSH HEADS** - Dual opposing heads sweep debris from both sides of cover during wind-up.
- BRISTLES** - Two rows of 3" bristles. One of black flagged styrene fiber for fine sweeping, the other of red polystyrene fiber for heavy debris. (See photo at left).



CALL TOLL FREE
1-800-693-1677

COVERMASTER™ COVERMASTER COVERMASTER

MASTERS IN THE ART OF SPORTS SURFACE COVERS



Learn more
covermaster.net
E-mail: info@covermaster.net

COVERMASTER INC., 3909 Witmer Road, Suite 187, Niagara Falls, NY 14305-1244 TEL. 716-304-1701